

Eco-Design-Regulation EU 2016/2281

Requirements for the documentation
(Appendix 2 / Chapter 5 / Table 15)

Product data

Unit	Xtend 1700
Type of liquefaction	W
Refrigerant/GWP	R513A / 631

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	6,69	---
Annual energy consumption	Q	131.286,26	kWh/a
Reduction factor C _{dc} of chillers	C _{dc}	0,9	---
Power regulation	---	abgestuft	---

Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P _A	118,60	kW
Rated power consumption	D _A	27,41	kW
Energy efficiency ratio	EER _{DC,A}	4,33	---

Parameter at assessment point B

Declared cooling capacity	P _B	110,69	kW
Declared power consumption	D _B	23,71	kW
Declared energy efficiency ratio	EER _{DC,B}	5,30	---

Parameter at assessment point C

Declared cooling capacity	P _C	102,79	kW
Declared power consumption	D _C	20,51	kW
Declared energy efficiency ratio	EER _{DC,C}	6,42	---

Parameter at assessment point D

Declared cooling capacity	P _D	94,88	kW
Declared power consumption	D _D	17,83	kW
Declared energy efficiency ratio	EER _{DC,D}	7,68	---